

CERTIFICATE OF CONFORMANCE

FOR

MATERIALS SHIPPED

Tulsa Gas Technologies, Inc. (TGT) hereby certifies that all materials in the manufacture of hoses for W/O # JWPC021425B conform to the manufacturing specifications indicated in drawings, bulletins or specifications as called for on the said purchase order. Test reports are on file with us or with our suppliers for examination and indicate conformance with applicable specification requirements. In production items listed, no direct contact was made with mercury, any of its compounds or with any mercury containing devices employing a single boundary for containment. Tulsa Gas Technologies, Inc. also certifies that the parts listed and shipped on the date indicated are manufactured in accordance with Parker specifications and quality standards, if applicable, as stated on the drawings or specifications called for on said purchase order. All parts and test conform to AGA I-93.

SIGNED BY: Patrick McElhenny
TITLE: Hose Builder
DATE: 7-30-25

Tulsa Gas Technologies, Inc.
4809 S. 101st. E. Ave.
Tulsa, OK 74146
918-665-2641

Work Order #
Customer Name
Customer PO
Date Required

JWPC021425B
JW Power
P1361289
2-14-25

ASSEMBLY/CERTIFICATION SHEET

- | | | SIGN | DATE |
|----|---|------|---------|
| 1 | ☒ Review shop work order versus customer print and history | PM | 7-30-25 |
| 2 | ☒ Component part numbers: <u>106CG-8-8, 106CG-8-8</u> | | |
| | Pack dates and/or QC codes | PM | 7-30-25 |
| 3 | ☒ ID band number <u>5220508622</u> | PM | 7-30-25 |
| 4 | ☒ Hose Cut Length <u>96"</u> | PM | 7-30-25 |
| 5 | Pre-expansion of hose (if required) Size | PM | 7-30-25 |
| | Remarks: | | |
| 6 | ☒ Audit and mark appropriate insertion depth | PM | 7-30-25 |
| 7 | Add special accessories | | |
| | Remarks: | | |
| 8 | ☒ Apply danger tag and ID band | PM | 7-30-25 |
| 9 | ☒ Install bend restrictors | PM | 7-30-25 |
| | Remarks: | | |
| 10 | ☒ Assemble fittings; check insertion depth | PM | 7-30-25 |
| | Remarks: | | |
| 11 | Set offset angle and/or orientation | PM | 7-30-25 |
| | Remarks: | | |
| 12 | ☒ Perform crimp or swage on product crimp set die using Parker Catalog 4660, page K58 | | |
| | ☒ 1/2) 80C-PO8H | | |
| | ☒ 1/4) 80C-PO4H | | |
| | ☒ 3/8) 80C-PO6 | | |
| | ☒ 3/8) 80C-PO6H | | |
| | ☒ 1/8) 80C-PO2 | | |
| | ☒ 3/4) 80C-P12H | PM | 7-30-25 |
| 13 | Add special accessories after crimping/swaging | | |
| 14 | Perform and record burst test results, if applicable | | |
| | Remarks: | | |
| 15 | Air test, if applicable | | |
| | Test pressure Psi _____ Seconds _____ ; Pass/Fail (Circle One) | | |
| | Remarks: | | |
| 16 | ☒ Hydrostatic proof test | | |
| | Test pressure Psi <u>10,000</u> Seconds <u>30</u> <u>Pass</u> Fail (Circle One) | | |
| | Remarks: | | |
| 17 | ☒ Flush method water, and then air | PM | 7-30-25 |
| 18 | ☒ Perform and record conductivity test: Meter _____ Megger Mit200 | PM | 7-30-25 |
| | Hose resistance <u>0.02</u> (-) Electrode resistance <u>0.03</u> | | |
| | (=) Final hose resistance <u>0.03</u> | PM | 7-30-25 |
| 19 | ☒ Final audit: Check boxes for items inspected, as applicable: | | |
| | ☒ Correct hose; ☒ Correct fittings; ☒ Correct customer PN | PM | 7-30-25 |
| 20 | ☒ Check swage or crimp diameters: | | |
| | <u>5CNG-6-58 .785/.805</u> ☒ <u>5CNG-4-58 .668/.688</u> | | |
| | <u>5CNG-6-55 .675/.695</u> ☒ <u>5CNG-8-58 .900/.920</u> | PM | 7-30-25 |
| | <u>5CNG-12-58 1.20/1.22</u> | | |
| | *****100% VISUAL INSPECT FOR THE FOLLOWING***** | | |
| 21 | ☒ Hose fittings crimped; ☒ Air passes through assembly; | | |
| | ☒ Presence of threads | PM | 7-30-25 |
| 20 | ☒ Cap and package hose | PM | 7-30-25 |
| 21 | ☒ Certificate of Conformance for Materials Shipped (on back) | PM | 7-30-25 |

3

FITTING TYPE

01 NPT MALE

02 NPT FEMALE

03 JIC MALE

04 SAE 45 MALE

05 SAE O-RING STRAIGHT THREAD

06 JIC FEMALE SWIVEL

07 FEMALE PIPE SWIVEL

7

FITTING SIZE

4 1/4"

6 3/8"

8 1/2"

12 3/4"

1

55 SERIES

HOSE SIZE

4 1/4"

6 3/8"

8 1/2"

12 3/4"

4

FITTING TYPE

01 NPT MALE

02 NPT FEMALE

03 JIC MALE

04 SAE 45 MALE

05 SAE O-RING STRAIGHT THREAD

06 JIC FEMALE SWIVEL

07 FEMALE PIPE SWIVEL

8

FITTING SIZE

4 1/4"

6 3/8"

8 1/2"

12 3/4"

BREAK-AWAY OR

DISPENSER END

11 FILL HOSE LENGTH

96"

FILL END

3 & 7

1 FILL

5 & 9

2 VENT

4 & 8

6 & 10

STANDARD 3" SHEREX 5/8" 5/8"

5

FITTING TYPE

01 NPT MALE

02 NPT FEMALE

03 JIC MALE

04 SAE 45 MALE

05 SAE O-RING STRAIGHT THREAD

06 JIC FEMALE SWIVEL

07 FEMALE PIPE SWIVEL

9

FITTING SIZE

2 1/8"

4 1/4"

6 3/8"

2

55 SERIES

HOSE SIZE

2 1/8"

4 1/4"

6 3/8"

6

FITTING TYPE

01 NPT MALE

02 NPT FEMALE

03 JIC MALE

04 SAE 45 MALE

05 SAE O-RING STRAIGHT THREAD

06 JIC FEMALE SWIVEL

07 FEMALE PIPE SWIVEL

10

FITTING SIZE

2 1/8"

4 1/4"

6 3/8"

WORK ORDER # JWP021425B

5CNG 8 / 520N 4 - 06 06 / 05 06 - 8 8 / 64 - 96"

FILL HOSE		TUSA GAS TIGHTENING, INC.	
DATE 01/09/03		10117 EAST 14TH STREET	
DESIGNED BY C. SEWELL		TUSA CR 74106	
DRAWN BY C.P.S.		910 605 2641 FAX 910 605 2657	
DWG. NO. FILLHOSE 5CNG-520N		CHECKED BY	
		SCALE NONE	
		SHEET NO. OF	
		REV. 2	

Tulsa Gas Technologies, Inc.
4809 S. 101st. E. Ave.
Tulsa, OK 74146
918-665-2641

Work Order #
Customer Name
Customer PO
Date Required

JWPC021425
JW Power
P1361284
2-14-25

ASSEMBLY/CERTIFICATION SHEET

- | | | SIGN | DATE |
|---|--|------|---------|
| 1 | ☒ Review shop work order versus customer print and history | PM | 7-30-25 |
| 2 | ☒ Component part numbers: <u>106CG-8-8, 106CG-8-8</u>
Pack dates and/or QC codes | PM | 7-30-25 |
| 3 | ☒ ID band number <u>5220508622</u> | PM | 7-30-25 |
| 4 | ☒ Hose Cut Length <u>36"</u> | PM | 7-30-25 |
| 5 | Pre-expansion of hose (if required) Size _____
Remarks: _____ | | |
| 6 | ☒ Audit and mark appropriate insertion depth | PM | 7-30-25 |
| 7 | Add special accessories _____
Remarks: _____ | | |
| 8 | ☒ Apply danger tag and ID band | PM | 7-30-25 |
| 9 | ☒ Install bend restrictors
Remarks: _____ | PM | 7-30-25 |
| 10 | ☒ Assemble fittings; check insertion depth
Remarks: _____ | PM | 7-30-25 |
| 11 | Set offset angle and/or orientation
Remarks: _____ | | |
| 12 | ☒ Perform crimp or swage on product/crimp set die using Parker Catalog 4660, page K58
<div style="display: flex; justify-content: space-between;"><div>☒ 1/2) 80C-PO8H</div><div>☐ 3/8) 80C-PO6H</div></div> <div style="display: flex; justify-content: space-between;"><div>☐ 1/4) 80C-PO4H</div><div>☐ 1/8) 80C-PO2</div></div> <div style="display: flex; justify-content: space-between;"><div>☐ 3/8) 80C-PO6</div><div>☐ 3/4) 80C-P12H</div></div> | PM | 7-30-25 |
| 13 | Add special accessories after crimping/swaging | | |
| 14 | Perform and record burst test results, if applicable
Remarks: _____ | | |
| 15 | Air test, if applicable
Test pressure Psi _____ Seconds _____ ; Pass/Fail (Circle One)
Remarks: _____ | | |
| 16 | ☒ Hydrostatic proof test
Test pressure Psi <u>10,000</u> Seconds <u>30</u> (<u>Pass</u>) Fail (Circle One)
Remarks: _____ | PM | 7-30-25 |
| 17 | ☒ Flush method water, and then air | PM | 7-30-25 |
| 18 | ☒ Perform and record conductivity test: Meter _____ Megger Mit200
Hose resistance <u>0.00</u> (-) Electrode resistance <u>0.03</u>
(=) Final hose resistance <u>0.03</u> | PM | 7-30-25 |
| 19 | ☒ Final audit: Check boxes for items inspected, as applicable:
<div style="display: flex; justify-content: space-between;"><div>☒ Correct hose;</div><div>☒ Correct fittings;</div><div>☒ Correct customer PN</div></div> | PM | 7-30-25 |
| 20 | ☒ Check swage or crimp diameters:
<div style="display: flex; justify-content: space-between;"><div>☒ 5CNG-4-58 .668/.688</div><div>☒ 5CNG-8-58 .900/.920</div></div> <div style="display: flex; justify-content: space-between;"><div>☒ 5CNG-6-58 .785/.805</div><div>☒ 5CNG-12-58 1.20/1.22</div></div> <div style="display: flex; justify-content: space-between;"><div>☒ 5CNG-6-55 .675/.695</div><div></div></div> | PM | 7-30-25 |
| *****100% VISUAL INSPECT FOR THE FOLLOWING***** | | | |
| 21 | ☒ Hose fittings crimped; ☒ Air passes through assembly;
☒ Presence of threads | PM | 7-30-25 |
| 20 | ☒ Cap and package hose | PM | 7-30-25 |
| 21 | ☒ Certificate of Conformance for Materials Shipped (on back) | PM | 7-30-25 |

3

FITTING TYPE

01 NPT MALE

02 NPT FEMALE

03 JIC MALE

04 SAE 45 MALE

05 SAE O-RING STRAIGHT THREAD

06 JIC FEMALE SWIVEL

07 FEMALE PIPE SWIVEL

7

FITTING SIZE

4 1/4"

6 3/8"

8 1/2"

12 3/4"

1

55 SERIES

HOSE SIZE

4 1/4"

6 3/8"

8 1/2"

12 3/4"

4

FITTING TYPE

01 NPT MALE

02 NPT FEMALE

03 JIC MALE

04 SAE 45 MALE

05 SAE O-RING STRAIGHT THREAD

06 JIC FEMALE SWIVEL

07 FEMALE PIPE SWIVEL

8

FITTING SIZE

4 1/4"

6 3/8"

8 1/2"

12 3/4"

BREAK-AWAY OR

DISPENSER END

11 FILL HOSE LENGTH

36"

3 & 7

5 & 9

2 VENT

1 FILL

6 & 10

4 & 8

STANDARD 3" }
SHEREX 5/8" }

5

FITTING TYPE

01 NPT MALE

02 NPT FEMALE

03 JIC MALE

04 SAE 45 MALE

05 SAE O-RING STRAIGHT THREAD

06 JIC FEMALE SWIVEL

07 FEMALE PIPE SWIVEL

9

FITTING SIZE

2 1/8"

4 1/4"

6 3/8"

2

55 SERIES

HOSE SIZE

2 1/8"

4 1/4"

6 3/8"

6

FITTING TYPE

01 NPT MALE

02 NPT FEMALE

03 JIC MALE

04 SAE 45 MALE

05 SAE O-RING STRAIGHT THREAD

06 JIC FEMALE SWIVEL

07 FEMALE PIPE SWIVEL

10

FITTING SIZE

2 1/8"

4 1/4"

6 3/8"

WORK ORDER # JWP021425B

1 2 3 4 5 6 7 8 9 10 11
5CNG 8 / 520N 4 - 06 06 / 05 06 - 8 8 / 04 - 36"

FILL HOSE

DATE 01/09/03

DESIGNED BY C. SEWELL

DRAWN BY C. S.

DWG. NO. FILLHOSE 5CNG 520N

SCALE NONE

SHEET NO. OF

REV. 2

LORSA GAS TIGHT EQUIPMENT, INC.
10117 EAST 94TH STREET
LORSA, OK 73146

918.605.2641 FAX 918.605.2657

CHECKED BY

SCALE NONE

SHEET NO. OF

REV. 2