

Part Number: BV708-4K6LDDN-1000



<https://configurator.oasisngv.com/B/BVV/1/4/NPT/NOVENT/6/L/DDN/Product10.html>

Type

Ball Valves with Vent Port or Vent Valve

Up to 410 bar. Suitable for use with CNG, Helium, Bio-Gas, Nitrogen, Hydrogen, Air and other gases on enquiry.

The 700 Series Ball Valve is a FULL FLOW, Anti Blowout stem, all stainless steel certified bar stock, two-piece, serviceable valve.

Service kits are readily available & easy to install. CNC machining allows tighter tolerances to be maintained, which extends the working life of the components.

The complete Oasis range has been cycle tested to ensure LOWEST LIFE COST.

Certificates: PED 2014/68/EU approved

Size

708 Ball Valve with Vent — 1"

Material Body

304 Stainless Steel

Connection

NPT female

NPT threads conform to ASME B1.20.1



Vent

With Vent Port

Up to 410 bar. Suitable for use with CNG Compressors, Dispensers, Priority Panels, Isolation Valves and storage.



Ball / Stem specifications **Both 316 Stainless Steel**

Seat Type **Extended pressure range (7 - 6000 psi / 0,5 - 410 bar)**

Seal / Seat Material **Nitrile / Delrin**

Contact Data:

Oasis Engineering (2003) Limited
129 Birch Avenue, Tauranga, 3110
New Zealand
Phone No.: +64-7-928-3808
Fax No.: +64-7-928-3809
General Enquiries: info@oasisngv.com
Sales Enquiries: sales@oasisngv.com
Acc. Enquiries: accounts@oasisngv.com
Internet: <https://www.oasisngv.com>