

NUTRON® Floating Ball Valves

ORDERING INFORMATION

How to develop figure numbers:

MODEL	BORE	SIZE		STYLE
		T3 - 3 PIECE THREADED B3 - 3 PIECE BOLTED	R - REGULAR F - FULL PORT V - VENTURI	

END CONNECTION	PRESSURE	OPTIONS
A - RAISED FACE / SMOOTH FACE B - BW SCH40 C - BW SCH80 D - BW SCH 160 E - BW SCH XXH F - FNPT X MNPT G - FNPT X RF H - FNPT X RTJ J - RTJ K - FLAT FACE	M - MALE NPT P - MALE EUE R - RAISED FACE S - FEMALE NPT T - FNPT X SW TS - FNPT X SW (Short) U - FEMALE EUE W - SOCKET WELD WS - S.W. (Short) X - SPECIAL	10 - 1000 WOG 14 - 1500 WOG 20 - 2000 WOG 30 - 3000 WOG 40 - 4000 WOG 60 - 6000 WOG
		01 - 150 ANSI 03 - 300 ANSI 06 - 600 ANSI 09 - 900 ANSI 15 - 1500 ANSI 25 - 2500 ANSI A2 - 2000 API A3 - 3000 API A5 - 5000 API

Examples:

T3-R07S20B = 3/4" RP 2000 WOG Female NPT, Standard Service, Model T3

T3-F05R15A = 1/2" FP ANSI 1500 RF, SS Valve -50°F, Model T3

T3-F15G06S = 1 1/2" FP FNPT x ANSI 600 RF, Sour Service, Model T3

Please consult our Sales Department for a full range of options, optional materials, actuation packages or special applications not listed.