

## DIN rail perforated - NS 35/15 PERF 2000MM - 1201730

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 mm

### Why buy this product

- ☒ If you require greater quantities, the same article is available in a unit pack of 25 pcs. (50 m)

RoHS

### Key Commercial Data

Packing unit	2 M
Minimum order quantity	5 M
GTIN	 4 017918 017460
GTIN	4017918017460
Weight per Piece (excluding packing)	1.000 g
Custom tariff number	72166190
Country of origin	Germany

### Technical data

#### Dimensions

Height	15 mm
Length	2000 mm
Width	35 mm

#### General

Material	Steel
Coating	Galvanized, passivated with a thick layer
Color	silver

# DIN rail perforated - NS 35/15 PERF 2000MM - 1201730

## Technical data

### General


Test standard	In acc. with EN 60715: 2001
---------------	-----------------------------

### Standards and Regulations

Test standard	In acc. with EN 60715: 2001
Connection in acc. with standard	IEC / EN

## Drawings

Dimensional drawing



## Classifications

### eCl@ss

eCl@ss 4.0	23150301
eCl@ss 4.1	23150301
eCl@ss 5.0	27141143
eCl@ss 5.1	27141143
eCl@ss 6.0	27141143
eCl@ss 7.0	27141143
eCl@ss 8.0	27400602
eCl@ss 9.0	27400602

### ETIM

ETIM 2.0	EC001285
ETIM 3.0	EC001285
ETIM 4.0	EC000212
ETIM 5.0	EC000212
ETIM 6.0	EC001285

## DIN rail perforated - NS 35/15 PERF 2000MM - 1201730

### Classifications

#### UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708
UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121708