



- 1 STUDS ARE 7/32" (.2187) ϕ , AND PLACED AS DIMENSIONED. STUDS ARE 1" (1.00) IN HEIGHT.
- 2 WINDOW SLOTS REQUIRE AN 1/8" (.1250) RADI ON ALL CORNERS.
- 3 HOLE IS ϕ 7/8" (.875) FOR PUSH BUTTON PLACEMENT.
- 4 KEYWAY IS 5/8" (.625) X 3/4" (0.75) WITH A RADI OF 3/4" ON EITHER END. PLACEMENT IS CENTERED OFF THE FRONT RIGHT EDGE AS DIMENSIONED ABOVE.
- 5 SLOTTED HOLE 3" X 7/32" PLACED AS DIMENSIONED
- 6 HINGE PIECES BOTH SIDES OF INSIDE OF PANEL. HOLES OF HINGE PIECES MUST MEET IN RELATIONS WITH 1/4 DIA. HOLES ON TOP AND BOTTOM SIDES OF THE PANEL.

NOTE: POST-FABRICATION DETAILING NOT SHOWN ON THIS DRAWING:
 (1) Company Decals
 (2) Push Button Installation
 (3) Electronics

MATERIAL IS COLD ROLLED STEEL

SEE BILL FOR DETAIL NOTES
 SCALE
 0.50" (1/2") = 6" or .5 MU = 6 DU
 SHOWN IN DECIMAL INCHES

TOLERANCES

.X	+/-	.06
.XX	+/-	.03
.XXX	+/-	.015
ANGLES	+/-	1

TULSA GAS TECHNOLOGIES, INC.
 4809 South 101st East Avenue
 Tulsa, OK 74146
 (918) 665-2641

MODEL:	TGT-7000-DH100	DRAWN BY:	MB	DATE:	07-27-06
SEQUENCE:	-	CHECKED BY:	-	PROGRAM:	-
SERIAL NO.:	-	APPROVED BY:	-	PART:	FACE PLATE
WORK ORDER:	-	DWG/PART NO.:	TGT-7010FP1	W LIGHTS:	-

NOTE A: Weld and grind smooth.

NOT TO SCALE